



Manufacturer & Marketed by:

DK Resources International Ltd.
 Room 105, 1/F., Fo Tan Industrial Building, 26-28 Au Pui Wan Street, Fo Tan, Sha Tin, New Territories, Hong Kong
 Tel: +852-68906866; +65-90180938; +86-13710298668
 Fax: +65-62342036
 E-mail: DSS168@hotmail.com; DSS-Sales168@hotmail.com; dannyk88@singnet.com.sg

Model No. (Brand)

DSS



**Deluxe
 Shelving
 System**

Product Description

Quality Shelving & System

Origin

China

Specifications

Function

Strong, reliable and durable shelving and system for storage (wet or dry) and can sustain the temperature down to -38°C.

Form

Modular structure of shelving with flexibility to add on and to construct shelf units in different forms & configuration.

Technical Specifications

Shelving (Vented Starter Units):

Width: 355mm (14"); 455mm (18"); 530mm (21"); 610mm (24")
 Length: 910mm (36"); 1060mm (42"); 1220mm (48");
 1370mm (54"); 1525mm (60"); 1825mm (72")
 Height: 1600mm (64"); 1800mm (72"); 2000mm (79")

Dunnage Racks:

Width: 355mm (14"); 455mm (18"); 530mm (21"); 610mm (24")
 Length: 910mm (36"); 1060mm (42"); 1220mm (48");
 1370mm (54"); 1525mm (60"); 1825mm (72")
 Height: 225mm (9")

Construction

DSS Shelving components (posts, traverses) are made of a steel core with polypropylene exterior to provide exceptional strength and durability.

	<p>DSS Shelving is weld-less. Hence, no liquid and dirt can get inside the crevices.</p> <p>DSS shelving will not rust as there is no metal exposed for all shelving parts and therefore every component can be safely washed in a commercial dishwasher.</p> <p>DSS shelving is designed and made in a modular system that allows the flexibility to assemble shelving to fit any sized area by adding to the Basic Unit for shelf extension and formation in any shape as desired.</p> <p>DSS Shelving can be even used in a subzero temperature as low as to minus 38°C.</p>
<u>Engineering / Site Preparation</u>	Measure the site (storage area) for proper space available and then select the right size of shelving that would fit the space allocated for the shelving.
<u>Capacity</u>	<p>A DSS Basic Shelf Unit is composed of 4 shelves as standard. Shelves can be adjusted in every 100mm increment.</p> <p>Weigh bearing of a Basic Shelf Unit with four shelves can be up to 1000kg, or 250kg per shelf.</p> <p>With a dunnage stand, the weight bearing could increase up to 450kg for the bottom shelf.</p>
<u>Sanitation</u>	Every component of DSS Shelving can be safely washed in a commercial dishwasher.
<u>Safety</u>	DSS Shelving has been approved and certified by NSF to ensure the food safety compliance.
<u>Special Requirements</u>	With only use of a mallet (rubber hammer), DSS Shelving can be easily assembled in minutes.